



# 5289

## Mobile Resonating Inductor 100kVA, 15kV

*Datasheet*



# HAEFELY

Current and voltage – our passion

Designed by



# General Description

The 5289 provides a motorized tunable 15 kV, 100 kVA inductor coil to be used together with the MIDAS 2881 system and increase its test object capacitance range, typically used on large rotating machines or other high capacitive load while testing on-site.

The variable inductor is connected in parallel with the capacitive test object CX forming a parallel resonant circuit. By adjusting the inductance the resonant point can be reached. At this resonance point the inductor

compensates the reactive power required by the DUT capacitance and only the small portion of real power (ohmic losses) is needed to be fed by the Midas 2881.

This arrangement enables measurement of capacitances up to 1.41  $\mu\text{F}$  at 15 kV .

## Features

- Max. Operating Voltage 15 kV rms (50 Hz/60 Hz)
- Frequency 50/60 Hz
- Output Power up to 100 kVA
- Reduced PD level (< 500pC)
- Mobile

# Applications

Combined with MIDAS 2881 it can be used for.

- Measuring power factor (capacitance and  $\tan \delta$ ) of rotating machines on site
- Measuring partial discharges of large rotating machines on site (requires DDX9121b and 9230)

## Scope of Supply

- 5289 resonating inductor
- Base load capacitor 400 nF
- Connection cable set MIDAS (3 m)
- Connection cable base load capacitor (20 m)

## Technical Data

Measurement	
Max. Operating Voltage	15 kV rms (50 Hz / 60 Hz)
Frequency	50 / 60 Hz
Max. Output Current	6.7 A @ 50Hz
Max. Output Power	100 kVA
Resistance	22.5 $\Omega$ @ 20 °C
Load tuning range <sup>(1)</sup>	0 .. 1.41 $\mu$ F @ 50 Hz * 0 .. 1.18 $\mu$ F @ 60 Hz *
PD level	< 500 pC
Duty cycle at full load	5 min ON / 1h OFF at rated output power. 1h ON / 1h OFF at 50% rated power

\* use additional base load capacitor if load < 250nF

Environmental	
Operating temperature	-10 °C +50 °C
Storage temperature	-20 °C +70 °C
Humidity	5 .. 95 % r.h.

Mechanical	
Dimensions (W x D x H)	55 x 71 x 108 cm (22 x 28 x 43 ")
Weight	376 kg (825 lb)

## Global Presence

### Europe

HAEFELY AG  
Birsstrasse 300  
4052 Basel  
Switzerland

☎ + 41 61 373 4111  
✉ [sales@haefely.com](mailto:sales@haefely.com)

### China

HAEFELY AG Representative Office  
8-1-602, Fortune Street, No. 67  
Chaoyang Road, Beijing 100025  
China

☎ + 86 10 8578 8099  
✉ [sales@haefely.com.cn](mailto:sales@haefely.com.cn)

This document has been drawn up with the utmost care. We cannot, however, guarantee that it is entirely complete, correct or up to date.  
©Copyright HAEFELY/ Subject to change without notice

V2023.03



# HAEFELY

Current and voltage – our passion



HIGH VOLTAGE



INSTRUMENTS



EMC

precision.  
  
swiss made.