

## FRA / V

# Reference functional check set

Datasheet







### **General Description**

The FRA /V is a compactly designed functional check set with four test objects rated at -20dB, -40dB, -60dB and -80dB.

A fast functional check of FRA 5311 among others is possible by connecting each unit to the device and observing the resulting measuring curve.

Features	Advantages
<ul> <li>BNC connections available</li> </ul>	☑ Flexible connection to the measuring instrument
Four calibrated test objects	☑ Allows for a complete range check
Delivered in a carrying case	☑ Stable and reliable ceaseless operation

#### **Applications**

Fast functional check of frequency response analyser instruments as;

FRA 5311

#### Scope of Supply

- -20dB functional check
- -40dB functional check
- -60dB functional check
- -80dB functional check
- BNC T-Adapter
- Carrying case
- Test certificate.

#### **Technical Data**

Measurement	
Frequency Range	10 Hz 1 MHz
Voltage input	max. 11 Vpp
Feasible accuracy	
Functional check -20dB	$\pm0.2dB$
Functional check -40dB	± 0.2 dB
Functional check -60dB	$\pm0.2dB$
Functional check -80dB	± 0.5 dB

Environmental	
Operating temperature	0°C +55°C
Storage temperature	-20°C +70°C
Humidity	5 90% r.h. , non-condensing
Mechanical	
Dimensions (W x D x H)	350 x 260 x 80 mm
Weight	750g Complete set and case

#### **Global Presence**

Europe

HAEFELY AG Birsstrasse 300 4052 Basel Switzerland

**+** 41 61 373 4111

sales@haefely.com

China

HAEFELY AG Representative Office 8-1-602, Fortune Street, No. 67 Chaoyang Road, Beijing 100025 China

**+** 86 10 8578 8099

sales@haefely.com.cn

This document has been drawn up with the utmost care. We cannot, however, guarantee that it is entirely complete, correct or up to date. ©Copyright HAEFELY/ Subject to change without notice

V2023.08





**EMC** 

