



TP

Stromwandler

Current Transformer

Transformateur de courant

- Zweiteiliger Stromwandler
- Polycarbonat-Schalenbauweise
- Für Innenraum-Anwendungen
- Befestigung auf Stromschiene oder mit Steckfüßen

- Split core current transformer
- Polycarbonate shell design
- For indoor application
- Mounting on primary bar or with plugged pedestals

- Transformateur de courant ouvrant
- Boîtier Polycarbonate
- Pour application intérieure
- Fixation au barre primaire ou avec des socles de fixation

Technische Daten

Höchste Betriebsspannung	0.72 kV
Prüfspannung	3.0 kV
Frequenz	50/60 Hz
Thermischer Dauerstrom	100% I _{pr}
Thermischer Kurzzeitstrom	60 I _{pr} 1s

Technical data

Highest operating voltage	0.72 kV
Test voltage	3.0 kV
Frequency	50/60 Hz
Continuous thermal current	100% I _{pr}
Short-time thermal current	60 I _{pr} 1s

Spécifications

Tension de service maximale	0.72 kV
Tension d'essai	3.0 kV
Fréquence	50/60 Hz
Courant thermique continu	100% I _{pr}
Courant de court-circuit thermique	60 I _{pr} 1s

This document has been drawn up with the utmost care. We cannot, however, guarantee that it is entirely complete, correct or up-to-date.

© Copyright PFIFFNER / Subject to change without notice. 2022.09



Current and voltage – our passion

PFIFFNER Messwandler AG

CH-5042 Hirschthal
www.pfiffner-group.com

HV HIGH VOLTAGE

MV MEDIUM VOLTAGE

LV LOW VOLTAGE

HS HOCHSPANNUNG

MS MITTELSPANNUNG

NS NIEDERSPANNUNG



Typ/Type/Type	I_{pr}/I_{sr}	cl. 0.5 VA	cl. 1 VA	cl. 3 VA	Abmessungen innen mm	Abmessungen aussen mm
TQ-6	100/5	-	1	2	20x30	80x91x28
TQ-6	150/5	-	1	2	20x30	80x91x28
TQ-6	200/5	0.5	1	2	20x30	80x91x28
TQ-6	250/5	0.5	1	2	20x30	80x91x28
TQ-6	300/5	0.5	1	2	20x30	80x91x28
TQ-6	400/5	1	2	4	20x30	80x91x28
TQ-8	300/5	1	2	4	60x80	120x148.5x28
TQ-8	400/5	1.5	2	4	60x80	120x148.5x28
TQ-8	500/5	3	4	8	60x80	120x148.5x28
TQ-8	600/5	3	4	8	60x80	120x148.5x28
TQ-8	700/5	5	8	16	60x80	120x148.5x28
TQ-8	750/5	5	8	16	60x80	120x148.5x28
TQ-8	800/5	5	8	16	60x80	120x148.5x28
TQ-8	1000/5	5	8	16	60x80	120x148.5x28
TQ-10	500/5	-	4	12	121x80	150x197x72
TQ-10	600/5	-	5	12	121x80	150x197x72
TQ-10	750/5	-	15	30	121x80	150x197x72
TQ-10	800/5	-	15	30	121x80	150x197x72
TQ-10	1000/5	-	15	25	121x80	150x197x72
TQ-10	1200/5	5	15	25	121x80	150x197x72
TQ-10	1250/5	7.5	25	30	121x80	150x197x72
TQ-10	1500/5	10	25	30	121x80	150x197x72
TQ-10	1600/5	10	25	30	121x80	150x197x72
TQ-10	2500/5	15	30	30	121x80	150x197x72
TP 88	250/5	-	2	4	80x80	144x145x50
TP 88	300/5	1.5	3	6	80x80	144x145x50
TP 88	400/5	1.5	3	10	80x80	144x145x50
TP 88	500/5	2.5	5	15	80x80	144x145x50
TP 88	600/5	2.5	5	17.5	80x80	144x145x50
TP 88	750/5	3	6	18	80x80	144x145x50
TP 88	800/5	3	7	18	80x80	144x145x50
TP 88	1000/5	5	10	20	80x80	144x145x50



Typ/Type/Type	I_{pr}/I_{sr}	cl. 0.5 VA	cl. 1 VA	cl. 3 VA	Abmessungen innen mm	Abmessungen aussen mm
TP-812	500/5	-	4	12	80x120	144x185x50
TP-812	600/5	-	5	14	80x120	144x185x50
TP-812	750/5	-	6	17	80x120	144x185x50
TP-812	800/5	-	7	18	80x120	144x185x50
TP-812	1000/5	-	9	20	80x120	144x185x50
TP-812	1200/5	6	11	24	80x120	144x185x50
TP-812	1250/5	7	15	28	80x120	144x185x50
TP-812	1500/5	8	17	30	80x120	144x185x50
TP-812	2500/5	10	17	25	80x120	144x185x50
TP-816	500/5	3	-	-	80x160	184x245x70
TP-816	600/5	3	-	-	80x160	184x245x70
TP-816	750/5	5	-	-	80x160	184x245x70
TP-816	1000/5	10	15	20	80x160	184x245x70
TP-816	1250/5	8	-	-	80x160	184x245x70
TP-816	1500/5	15	20	25	80x160	184x245x70
TP-816	2000/5	15	20	25	80x160	184x245x70
TP-816	2500/5	15	20	25	80x160	184x245x70
TP-816	3000/5	20	25	30	80x160	184x245x70
TP-816	4000/5	20	25	30	80x160	184x245x70
TP-816	5000/5	20	25	30	80x160	184x245x70
TP-816	6000/5	20	-	-	80x160	184x245x70